

Replaceable LED Lamps for GH36d socket Austauschbare LED-Lampen für GH36d-Fassung

Highly efficient LED module for GH36d sockets with twist & lock system, designed for up to 32 W. Performance data see overview on the right. Versions with special LED chips available on request. Excellent uniformity of optical emission and colour over angle consistency. Exceptional long-term colour stability and thermal conductivity for even heat distribution. Module with B35 reflector/optics interface. Sustainable technology enables the modular light source to be easily replaced by the end user.

Hocheffizientes LED-Modul für GH36d-Fassungen mit Twist & Lock-Verschluss, ausgelegt für bis zu 32 W. Leistungsdaten siehe Übersicht rechts. Ausführungen mit Sonder-LED-Chips auf Anfrage möglich. Ausgezeichnete Gleichmäßigkeit der optischen Emission und Farbkonsistenz über Winkel. Außergewöhnlich langfristige Farbstabilität und Wärmeleitfähigkeit für gleichmäßige Wärmeverteilung. Modul mit B35 Reflektor/Optik-Schnittstelle.

Nachhaltige Technologie ermöglicht das mühelose Austauschen des modularen Leuchtmittels durch den Endverbraucher.



Technical Data / Technische Daten

Socket/ Fassung:		GH36d-5			COB-Type: Regular											
Type of Lamp/ Lampen-Typ		CRI	CCT [K]	SDCM	Current/ Forward Voltage/ Power/	Stromstärke/ Vorwärtsspannung/ Leistung/	Pmax = 32 W @ 900 mA									
					[mA]	[V]	[W]	200	300	400	500	600	700	800	900	
CXM14G5-	927	90	2700	3	Energy Efficiency Class/	Energieeffizienzklasse		B	C	C	C	C	C	C	D	
					Lamp Luminous Flux/	Lampenlichtstrom	[lm]	1083	1593	2091	2579	3056	3522	3978	4424	
					Efficacy/	Effizienz	[lm/W]	172	166	162	158	154	151	148	145	
	930	90	3000	3	Energy Efficiency Class/	Energieeffizienzklasse		B	C	C	C	C	C	C	C	
					Lamp Luminous Flux/	Lampenlichtstrom	[lm]	1102	1621	2128	2624	3109	3583	4047	4501	
					Efficacy/	Effizienz	[lm/W]	175	169	165	161	157	154	150	147	
	935	90	3500	3	Energy Efficiency Class/	Energieeffizienzklasse		B	B	B	C	C	C	C	C	
					Lamp Luminous Flux/	Lampenlichtstrom	[lm]	1149	1691	2220	2738	3245	3739	4223	4697	
					Efficacy/	Effizienz	[lm/W]	182	176	172	168	164	160	157	153	
	940	90	4000	3	Energy Efficiency Class/	Energieeffizienzklasse		B	B	B	C	C	C	C	C	
					Lamp Luminous Flux/	Lampenlichtstrom	[lm]	1149	1691	2220	2738	3245	3739	4223	4697	
					Efficacy/	Effizienz	[lm/W]	182	176	172	168	164	160	157	153	

